



Dewatering Pump(3600RPM)

APPLICATIONS: Lifting of well water and underground water, aqua farm, agriculture irrigation, hydraulic engineering and drainage of subway...etc.

***Above head of 15 meters is applicable.**





BH-211A

BH-322SB

ABH-322SB
(Exclude check valve)

FEATURES

1. Two features (water delivery and extraction) in one design can be applied as a landed water pump by removing strainer and connecting a check valve.(limited to 3Hp and 5Hp)
2. Water-cooling jacket design prevents overheat after long time operation, and impeller is designed regards to slicing concept for high water volume and high head.
3. Adopted dual SIC Mech. Seal (above 3HP)
4. High head design for above 15 meters.
5. Motor frame and outer cover are made of stainless steel.
6. Check valve is available (option)



SPECIFICATIONS

2P-3600RPM

| Model | Output Hp (kW) | Discharge inch | Phase ϕ | Standards | | Max Diameter mm | Height mm | Weight kg |
|-----------|----------------|----------------|---------------------------|-----------|-----------------|-----------------|-----------|-----------|
| | | | | Head m | Capacity m³/min | | | |
| BH-211A | 1½ (1.1) | 2" | (1 ϕ 220v)/ 3 ϕ | 12 | 0.2 | 180 | 490 | 28 |
| BH-322SB | 3 (2.2) | 3" | (1 ϕ 220v)/ 3 ϕ | 15 | 0.5 | 245 | 530 | 52/47 |
| ABH-322SB | 3 (2.2) | 3" | (1 ϕ 220v)/ 3 ϕ | 15 | 0.5 | 245 | 530 | 50 |
| BH-422SB | 3 (2.2) | 4" | (1 ϕ 220v)/ 3 ϕ | 15 | 0.5 | 245 | 530 | 52/47 |
| ABH-422SB | 3 (2.2) | 4" | (1 ϕ 220v)/ 3 ϕ | 15 | 0.5 | 245 | 530 | 50 |
| BH-437SB | 5 (3.7) | 4" | 3 ϕ | 14 | 1.0 | 270 | 680 | 60 |
| BH-455U | 7½ (5.5) | 4" | 3 ϕ | 22 | 0.6 | 270 | 680 | 72 |
| BH-475S | 10 (7.5) | 4" | 3 ϕ | 25 | 1.0 | 380 | 840 | 90 |