



■ **APPLICATIONS:** A sprinkler for grass, garden, horticulture; irrigation for orchard; water spray for roof cleaning; wastewater treatment; drainage of basement and well water, and car wash...etc.



## FEATURES

1. Double impeller and pump housing design for BU-107.
2. Adopted dual mechanical seals provide long time operation.
3. Impeller is designed to special water flow, and corrosive-resistant and wear-resistant for high-head uses.
4. Motor frame, shaft, screws are made of stainless steel to make long service life and attractive appearance.
5. The base of cable is made out of integral plastic to upgrade humidity-resistance.

● Float switch is available for model under 2Hp.

## SPECIFICATIONS

2P-3600RPM

Model	Output Hp (kW)	Discharge inch	Phase $\phi$	Standards		Free Passage mm	Length mm	Width mm	Height mm	Weight kg
				Head m	Capacity m <sup>3</sup> /min					
BU-107	1 (0.75)	1"	(1 $\phi$ 220v)/ 3 $\phi$	20	0.04	3.2	230	195	450	21
BU-208	1½ (1.1)	2"	(1 $\phi$ 220v)/ 3 $\phi$	16	0.15	3.2	250	195	480	24
BU-215	2 (1.5)	2"	(1 $\phi$ 220v)/ 3 $\phi$	20	0.17	3.2	270	195	580/500	33/30
BU-322B	3 (2.2)	3"	3 $\phi$	20	0.3	3.2	420	240	550	40
BU-355A	7½ (5.5)	3"	3 $\phi$	30	0.5	5.5	470	250	570	61
BU-475	10 (7.5)	4"	3 $\phi$	32	0.6	5.5	560	310	690	91
BU-4110	15 (11)	4"	3 $\phi$	32	0.8	5.5	590	310	720	101